

CERTIFICATE OF ANALYSIS

C10 LINEAR ALPHA OLEFINS

Parameters	Unit	Specifications	Reference Method No.	Results
C10 Hydrocarbons	% wt	Min. 98.50	GC	99.853
Mono Olefins	% wt	Min. 99.00	GC	99.795
n-Alpha Olefins	% wt	Min. 90.00	GC	91.692
Branch Olefins	% wt	Max. 7.50	GC	5.811
Internal Olefins	% wt	Max. 3.00	GC	2.145
Paraffins	% wt	Max. 0.30	GC	0.111
Carbon No. > C10	% wt	Max. 1.50	GC	0.052
Amine	wt. ppm	Max. 1.00	GC	<0.3
Peroxide	mg/kg	Max. 1.00	ASTM E-299	0.70
Saybolt Color	-	Min. 30	ASTM D-6045	+30
Moisture	mg/kg	Max. 25.00	ASTM E-1064	10
Appearance	-	Clear & Bright	ASTM-E-2680	Clear& Bright

Shivtek Spechemi Industries Ltd

(Formerly known as Shshivtek Industries Private Limited)

CIN No. U24100DL2009PLC188730

📍 **Corp Office:** 1419, DLF Corporate Green Tower 1, Sector 74 A, Southern Peripheral Road (SPR), Gurugram, Haryana-122004 (India) Phone: +91-124-6904448

📍 **Regd Office:** Khasra No. 169, Ground Floor, Back Side, Alipur, Delhi- 110036

✉ **info@shivtekspechemi.com, sales@shivtekspechemi.com** 🌐 **www.shivtekspechemi.com**

