

CERTIFICATE OF ANALYSIS

C14 NORMAL PARAFFIN

Test	Test Method	Unit	Spec Limits	Results
Appearance	Visual		-	CLEAR
Density @ 15.5 Deg	ASTM D4052-22		765 to 775	768.2
Bromine Index	UOP 304-08	mg/100g	Max 25	0.50
Saybolt Color	ASTM D158-15		Min +30	+30
<C14	UOP 915-82	%	Max 1.0	0.07
C14	UOP 915-82	%	Min 95	99.21
>C14	UOP 915-82	%	Max 2.5	0.12
Total Normal Paraffin	UOP 915-82	%	Min 98.5	99.40
MNV	UOP 915-82		-	180.40
Total Sulfur	ASTM D5453-19a	ppm	Max 1.0	0.1
Aromatics	UOP 485-03	%	Max 0.20	0.08
Moisture Content	UOP 481-10	ppm	Max 100	95
Flash Point	ASTM D93-20	°C	Min 94.0	114.0
<i>Distillation</i>				
IBP	ASTM D86-20b	°C	-	242.00
FBP	ASTM D86-20b	°C	-	249.70

Shivtek Spechemi Industries Ltd

(Formerly known as Shhivtek Industries Private Limited)

CIN No. U24100DL2009PLC188730

● **Corp Office:** 1419, DLF Corporate Green Tower 1, Sector 74 A, Southern Peripheral Road (SPR), Gurugram, Haryana-122004 (India) Phone: +91-124-6904448

● **Regd Office:** Khasra No. 169, Ground Floor, Back Side, Alipur, Delhi- 110036

● **info@shivtekspechemi.com, sales@shivtekspechemi.com** ● **www.shivtekspechemi.com**

