

TECHNICAL DATA SHEET / CERTIFICATE OF ANALYSIS

ETRO 3

No.	Test Parameter	Method	Specification	Unit	Results
1.	Appearance	Visual	Bright & Clear	-	Bright & Clear
2.	Density @ 15 °C	ASTM D 4052	Report	kg/L	0.8266
3.	Color ASTM	ASTM D 1500	L0.5	-	L0.5
4.	K. Viscosity @ 40 °C	ASTM D 445	≥ 9.00	cSt	10.28
5.	K. Viscosity @ 100 °C	ASTM D 445	2.70 – 3.20	cSt	2.779
6.	Viscosity Index	ASTM D 2270	Report	-	114
7.	Pour Point	ASTM D 97	≤ - 27	°C	-39
8.	Flash Point (COC), °C	ASTM D 92	≥ 170	°C	182
9.	Sulphur Content	ASTM D 5453	Report	mg/kg	< 1.0
10.	#Saturated	ASTM D 7419	Report	mass %	99.4

Shivtek Spechemi Industries Ltd

(Formerly known as Shshivtek Industries Private Limited)

CIN No. U24100DL2009PLC188730

📍 **Corp Office:** 1419, DLF Corporate Green Tower 1, Sector 74 A, Southern Peripheral Road (SPR), Gurugram, Haryana-122004 (India) Phone: +91-124-6904448

📍 **Regd Office:** Khasra No. 169, Ground Floor, Back Side, Alipur, Delhi- 110036

✉ **info@shivtekspechemi.com, sales@shivtekspechemi.com** 🌐 **www.shivtekspechemi.com**

