

TECHNICAL DATA SHEET / CERTIFICATE OF ANALYSIS

FARASOL D120

Density @ 15°C	ASTM D 4052	829.9	kg/m ³	810	840
Appearance	Visual	Clear	-	-	
Saybolt Color	ASTM D 156	>30	-	30	
Flash Point	ASTM D 93	125.0	°C	115	
Aromatics	UOP 495 / UV Internal Method	78.0	ppm (w/w)		300
Sulfur Content	ASTM D 5453	0.69	ppm (w/w)		5
Viscosity @ 40°C	ASTM D 445	3.829	mm ² /s	-	
Pour Point	ASTM D 97	-60.0	°C		-40
Initial Boiling Point (IBP)	ASTM D 86	265.30	°C	250.00	
Final Boiling Point (FBP)	ASTM D 86	308.80	°C		320.00
** End of Analytical Results **					

Shivtek Spechemi Industries Ltd

(Formerly known as Shhivtek Industries Private Limited)

CIN No. U24100DL2009PLC188730

📍 **Corp Office:** 1419, DLF Corporate Green Tower 1, Sector 74 A, Southern Peripheral Road (SPR), Gurugram, Haryana-122004 (India) Phone: +91-124-6904448

📍 **Regd Office:** Khasra No. 169, Ground Floor, Back Side, Alipur, Delhi- 110036

✉ **info@shivtekspechemi.com, sales@shivtekspechemi.com** 🌐 **www.shivtekspechemi.com**

