

TECHNICAL DATA SHEET / CERTIFICATE OF ANALYSIS

HEAVY NORMAL PARAFFIN C14-C17

Method	Test	Unit	Result	Limit
ASTM D 4176	APPEARANCE AT 25 degC		Clear Liquid	=
RCM 3609	SAYBOLT COLOUR	No	>30	30 MIN
ASTMD 4052	DENSITY @ 15 degC	KG/M3	773,4	=
ASTM D 1492	BROMINE INDEX	mgBr2/100 g	4,00	20,0 MAX
RCM 5202	SULPHUR	mg/kg	<0,3	1,0 MAX
UOP 495	AROMATICS	wt%	0,0100	0,05 MAX
ASTM D 93	FLASH POINT	degC	>120	108 MIN
RCM 2703	TNP	wt%	99,7	98,0 MIN
RCM 2703	CARBON DISTRIBUTION			
RCM 1106	C13 and lighter	wt%	0,2	1,0 MAX
RCM 1106	C14	wt%	28,0	15,0 MIN - 42,0 MAX
RCM 1106	C15+C16+C17	wt%	68,40	=
RCM 1106	C18 and Heavier	wt%	3,1	5,0 MAX
RCM 1106	AVERAGE MOLECULAR WEIGHT	g/mole	215,0	209 MIN

Shivtek Spechemi Industries Ltd

(Formerly known as Shshivtek Industries Private Limited)

CIN No. U24100DL2009PLC188730

📍 **Corp Office:** 1419, DLF Corporate Green Tower 1, Sector 74 A, Southern Peripheral Road (SPR), Gurugram, Haryana-122004 (India) Phone: +91-124-6904448

📍 **Regd Office:** Khasra No. 169, Ground Floor, Back Side, Alipur, Delhi- 110036

✉ **info@shivtekspechemi.com, sales@shivtekspechemi.com** 🌐 **www.shivtekspechemi.com**

