

CERTIFICATE OF ANALYSIS

SHIVASOL MIXED PARAFFIN

PROPERTY	TEST METHOD	SPECIFICATION	TYPICAL VALUE
Total Paraffin	UOP 915	99 min.	99.5
Carbon Distribution, wt%	UOP 915		
C9-13		50% min	55%
C14 and Higher		50% max	45%
Aromatics, wt%	UOP 495	0.5 max	0.32
Density at 29.5 °C, gr/cm ³	ASTM D-4052	0.750-0.755	0.753
Moisture, ppm	UOP 481	100 max	4
Bromine-Index, mg Br/ 100gr of Sample	ASTM D- 1492	20 max	2
Nitrogen, ppm	ASTM D- 6366	1 max	< 0.5
Sulfur, ppm	ASTM D- 5453	2 max	< 1
Peroxide Number	ASTM E-299	2 max	< 0.1
Chloride, ppm	UOP 395	1 max	< 0.1
Saybolt Color	ASTM-D- 156	+29 min	>+30
Flash Point °c	ASTM D-93	60 min.	65

Shivtek Spechemi Industries Ltd

(Formerly known as Shhivtek Industries Private Limited)

CIN No. U24100DL2009PLC188730

📍 **Corp Office:** 1419, DLF Corporate Green Tower 1, Sector 74 A, Southern Peripheral Road (SPR), Gurugram, Haryana-122004 (India) Phone: +91-124-6904448

📍 **Regd Office:** Khasra No. 169, Ground Floor, Back Side, Alipur, Delhi- 110036

✉ **info@shivtekspechemi.com, sales@shivtekspechemi.com** 🌐 **www.shivtekspechemi.com**

