

TECHNICAL DATA SHEET / CERTIFICATE OF ANALYSIS

NORMAL PARAFFIN C10 (DECANE)

Method	Test	Unit	Result
ASTM D 4176	Appearance at 25°C	Adimensionale	Clear & Bright
ASTM D 4052	Density at 15°C	Kg/m ³	735,1
ASTM D 156	Saybolt colour	Adimensionale	+30
ASTM D 1492	Bromine index	mgBR2/100gr	6
ASTM D 5453	Sulfur	mg/kg	<0,50
UOP 495	Aromatics	% mass	0,21
RCM 1106	C9 and lighter	% mass	0,43
RCM 1106	C10	% mass	93,88
RCM 1106	C11 and heavier	% mass	4,46
RCM 1106	Total n-paraffins	% mass	98,50
RCM 1106	Average Molecular Mass	% mass	143
ASTM D 86	Initial Boiling Point	°C	167,5
ASTM D 86	Final Boiling Point	°C	196,7

Shivtek Spechemi Industries Ltd

(Formerly known as Shhivtek Industries Private Limited)

CIN No. U24100DL2009PLC188730

📍 **Corp Office:** 1419, DLF Corporate Green Tower 1, Sector 74 A, Southern Peripheral Road (SPR), Gurugram, Haryana-122004 (India) Phone: +91-124-6904448

📍 **Regd Office:** Khasra No. 169, Ground Floor, Back Side, Alipur, Delhi- 110036

✉ **info@shivtekspechemi.com, sales@shivtekspechemi.com** 🌐 **www.shivtekspechemi.com**

