

SHIVASOLTM 3D

HALOGENATED HYDROCARBONS

TECHNICAL DATA SHEET SHIVASOL LP 789

S. No	Test Parameters	Unit	Test Method	Specification	
1.	Description		Visual	<u>Min.</u> Colorless, Transparent, Oily Liquid	<u>Max.</u>
2	Color		HU	0	
3	Flash Point (COC)	°C	ASTM D 92	>80	
4	Pour Point	°C	ASTM D 97	<0	
5	Relative Density @ 30 °C	gm/ml	USP	0.780	0.790
6	Halogens	%	SGQC	5 max	
7	Hydrocarbon Content	%	SGQC	95 min.	
8	Sulfur Content	%	SGQC	NIL	
9	Water Content	%	SGQC	NIL	

Applications:-

- Information in this publication is believed to be accurate and is given in good faith, but it is for the customer to satisfy itself of the suitability for its own particular purpose. Accordingly, Shiva Group gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that such exclusion is prevented by law. Freedom under Patent, Copyright and Designs cannot be assumed.
- Samples kept for 12 hours at a specified temperature before conducting test.
- The specifications are solely checked by SHIVA in house Laboratory and are indicative. All specs needs to be cross examined before confirming commercial deals.
- This document cannot be used for any legal purpose.

Shivtek Spechemi Industries Ltd

(Formerly known as Shshivtek Industries Private Limited)

CIN No. U24100DL2009PLC188730

📍 Corp Office: 1419, DLF Corporate Green Tower 1, Sector 74 A, Southern Peripheral Road (SPR), Gurugram, Haryana-122004 (India) Phone: +91-124-6904448

📍 Regd Office: Khasra No. 169, Ground Floor, Back Side, Alipur, Delhi- 110036

✉ info@shivtekspechemi.com, sales@shivtekspechemi.com 🌐 www.shivtekspechemi.com

